





TYPE 3 (Four Layer)

Also available in:



Red



Black

Characteristics:

- High resistance to abrasion, oils, acids, chemicals, cracking, heat, adverse weather conditions, kinking, petroleum, ozone, etc
- No maintenance required; no drying required after use
- Easy to coil, wet or dry
- One of the few companies in the world to offer 4-layer hoses

Applications:

- Municipal fire brigades
- Industrial fire brigades
- Petrochemical Industries
- Navies
- Mining industries
- General industrial uses for delivery purposes

Approvals:

- UL Listing
- BS 6391:1983 (Type III)

Available Lengths:

- 20 Metres
- 23 Metres
- 30 Metres
- 60 Metres
- 100 Metres

Options:

- Available in different colours for Minimum Order Quantity orders
- Custom marking available for Minimum Order Quantity orders

Technical Specifications:

Inner Diameter		Work Pressure		Test Pressure		Burst Pressure	
<i>mm</i>	<i>inches</i>	<i>bar</i>	<i>psi</i>	<i>bar</i>	<i>psi</i>	<i>bar</i>	<i>psi</i>
25	1	30	450	60	900	90	1,350
38	1 ½	20	300	40	600	60	900
45	1 ¾	20	300	40	600	60	900
52	2	20	300	40	600	60	900
64	2 ½	20	300	40	600	55	825
70	2 ¾	20	300	40	600	50	750
75	3	20	300	40	600	50	750

Notes:

**** The information contained herein is believed to be true and correct; however, it is not warranted or certified for accuracy. Allwares shall not be liable for errors contained herein or for incidental consequential damages in connection with the use of this material. Any use or re-use of this information will be at the user's own risk. Please kindly enquiry for details and specific test reports!**

**** It is important to note that the above technical specifications stated above are only valid for hoses and not for hose assembly with couplings.**