





TYPE 3


Also available in:



Blue



Yellow



Black

**Characteristics:**

- Manufactured to withstand a wide range of chemical products: oil, hydrocarbons, acids, alkalis, salt water, etc
- Provides consistent flexibility and elasticity (prevents kinking)
- No maintenance required; no drying required after use
- Protected against ozone, ultraviolet and atmospheric weather

**Applications:**

- Municipal fire brigades
- Industrial fire brigades
- Petrochemical Industries
- Navies
- Mining industries
- General industrial uses for delivery purposes

**Approvals:**

- Maritime and Coastguard Agency (MCA)
- American Bureau of Shipping (ABS)
- Australian Standard (AS)
- Det Norske Veritas (DNV)
- DIN 14 811
- Factory Mutual (FM)
- Lloyd's Register
- UL Listing
- BS 6391:1983 (Type III)

**Available Lengths:**

- 20 Metres
- 23 Metres
- 30 Metres
- 60 Metres
- 100 Metres

120 Hillview Avenue #06-01 Kewalram Hillview Singapore 669594

Telephone: +65 6769-9249 Facsimile: +65 6762-1854 Email: [info@allwares.com.sg](mailto:info@allwares.com.sg)

**Options:**

- Available in different colours for Minimum Order Quantity orders
- Custom marking available for Minimum Order Quantity orders
- Also available in 'rib less' version

**Technical Specifications:**

| Inner Diameter |               | Work Pressure |            | Test Pressure |            | Burst Pressure |            |
|----------------|---------------|---------------|------------|---------------|------------|----------------|------------|
| <i>mm</i>      | <i>inches</i> | <i>bar</i>    | <i>psi</i> | <i>bar</i>    | <i>psi</i> | <i>bar</i>     | <i>psi</i> |
| 25             | 1             | 25            | 375        | 40            | 600        | 90             | 1,350      |
| 38             | 1 ½           | 20            | 300        | 40            | 600        | 60             | 900        |
| 45             | 1 ¾           | 20            | 300        | 40            | 600        | 60             | 900        |
| 52             | 2             | 17            | 255        | 32            | 480        | 50             | 750        |
| 64             | 2 ½           | 17            | 255        | 32            | 480        | 50             | 750        |
| 70             | 2 ¾           | 17            | 255        | 32            | 480        | 50             | 750        |
| 75             | 3             | 14            | 210        | 27            | 405        | 48             | 720        |
| 102            | 4             | 14            | 210        | 27            | 405        | 48             | 720        |

**Notes:**

*\*\* The information contained herein is believed to be true and correct; however, it is not warranted or certified for accuracy. Allwares shall not be liable for errors contained herein or for incidental consequential damages in connection with the use of this material. Any use or re-use of this information will be at the user's own risk. Please kindly enquiry for details and specific test reports!*

*\*\* It is important to note that the above technical specifications stated above are only valid for hoses and not for hose assembly with couplings.*