



TYPE 1



TYPE 2

**Characteristics:**

- Low friction losses
- Aging and ozone resistant
- Ultra-light for easy handling
- Excellent value for money
- PU coating for substantial improvement in resistance to abrasion and chemicals (Type 2)

**Applications:**

- Municipal fire brigades
- Industrial fire brigades
- Ships and offshore applications
- Refineries
- Delivery purposes

**Approvals:**

- DIN 14 811
- ONORM
- Lloyd's Register
- SBG
- Germanischer Lloyd
- LOBA

**Available Lengths:**

- 20 Metres
- 23 Metres
- 30 Metres
- 60 Metres
- 100 Metres

**Options:**

- Double-jacketed hose
- Special non-toxic liner for the food industry
- Custom marking available for Minimum Order Quantity orders

**Technical Specifications:**

Inner Diameter		Work Pressure		Test Pressure		Burst Pressure	
<i>mm</i>	<i>inches</i>	<i>bar</i>	<i>psi</i>	<i>bar</i>	<i>psi</i>	<i>bar</i>	<i>psi</i>
25	1	20	300	40	600	90	1,350
38	1 ½	14	210	28	420	60	900
45	1 ¾	14	210	28	420	50	750
52	2	14	210	28	420	50	750
64	2 ½	14	210	28	420	50	750
70	2 ¾	14	210	28	420	50	750
75	3	14	210	28	420	45	675
102	4	12	180	25	375	35	525

**Notes:**

*\*\* The information contained herein is believed to be true and correct; however, it is not warranted or certified for accuracy. Allwares shall not be liable for errors contained herein or for incidental consequential damages in connection with the use of this material. Any use or re-use of this information will be at the user's own risk. Please kindly enquiry for details and specific test reports!*

*\*\* It is important to note that the above technical specifications stated above are only valid for hoses and not for hose assembly with couplings.*