



### ANTI-STATIC HOSE

Model Name: ALTRA-ANTIS™ Hose

#### Characteristics:

- Anti-static properties (Electric resistant certified to ISO2883:1980 & 2878:1987 standards)
- High abrasion resistance level
- Resistance to oil, fuel and a wide range of chemicals
- Very flexible and lightweight, as compared to mandrel-built hoses (saves warehouse space)
- Resistant to high temperatures
- No cleaning and drying required

#### Applications:

- Fuel/ petrol discharge, refuelling, etc
- Fire-fighting in hazardous, flammable environments
- Tank cleaning
- Refineries
- Oil rigs
- Transfer of chemical products
- Bypass in oil pipelines
- Breakdown and maintenance

#### Standard Lengths:

- 15 Metres
- 30 Metres
- 60 Metres
- 100 Metres

#### Options:

- Available in different colours for Minimum Order Quantity orders
- Custom marking available for Minimum Order Quantity orders

**Technical Specifications:**

<b>Inner Diameter</b>		<b>Work Pressure</b>		<b>Test Pressure</b>		<b>Burst Pressure</b>	
<i>mm</i>	<i>inches</i>	<i>bar</i>	<i>psi</i>	<i>bar</i>	<i>psi</i>	<i>bar</i>	<i>psi</i>
25	1	30	450	60	900	> 90	> 1,350
38	1 ½	20	300	40	600	> 60	> 900
52	2	20	300	40	600	> 60	> 900
64	2 ½	16	240	35	525	>50	>750
75	3	15	225	30	450	>45	>675
102	4	14	210	28	420	>42	>630

**Notes:**

*\*\* The information contained herein is believed to be true and correct; however, it is not warranted or certified for accuracy. Allwares shall not be liable for errors contained herein or for incidental consequential damages in connection with the use of this material. Any use or re-use of this information will be at the user's own risk. Please kindly enquiry for details and specific test reports!*

*\*\* It is important to note that the above technical specifications stated above are only valid for hoses and not for hose assembly with couplings.*